

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 709 872 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
21.04.1999 Bulletin 1999/16

(51) Int Cl.⁶: **H01J 29/07**

(21) Application number: **95116896.2**

(22) Date of filing: **26.10.1995**

(54) **Color cathode ray tube apparatus**

Farbkathodenstrahlröhre

Tube à rayons cathodique couleur

(84) Designated Contracting States:
DE FR GB IT NL

(30) Priority: **28.10.1994 JP 265081/94**
31.10.1994 JP 267007/94

(43) Date of publication of application:
01.05.1996 Bulletin 1996/18

(60) Divisional application: **97106464.7 / 0 788 133**

(73) Proprietor: **Matsushita Electronics Corporation**
Takatsuki-shi, Osaka 569-1143 (JP)

(72) Inventors:
• **Maki, Hideaki**
Sakai-shi, Osaka 590-01 (JP)
• **Araya, Jun**
Takatsuki-shi, Osaka 569-11 (JP)
• **Ishibashi, Mayumi**
Moriguchi-shi, Osaka 570 (JP)
• **Okamoto, Takami**
Muko-shi, Kyoto 617 (JP)

(74) Representative: **VOSSIUS & PARTNER**
Siebertstrasse 4
81675 München (DE)

(56) References cited:
EP-A- 0 228 110 **EP-A- 0 602 620**
GB-A- 2 001 193 **GB-A- 2 240 659**
US-A- 4 069 567 **US-A- 4 333 034**
US-A- 5 218 267

- **PATENT ABSTRACTS OF JAPAN vol. 015, no. 442 (E-1131), 11 November 1991 & JP-A-03 187132 (HITACHI LTD), 15 August 1991,**
- **PATENT ABSTRACTS OF JAPAN vol. 016, no. 318 (E-1232), 13 July 1992 & JP-A-04 092337 (SUMITOMO METAL MINING CO LTD), 25 March 1992,**
- **PATENT ABSTRACTS OF JAPAN vol. 014, no. 493 (E-0995), 26 October 1990 & JP-A-02 204943 (MITSUBISHI ELECTRIC CORP), 14 August 1990,**
- **PATENT ABSTRACTS OF JAPAN vol. 004, no. 133 (E-026), 18 September 1980 & JP-A-55 086049 (TOSHIBA CORP), 28 June 1980,**

Remarks:

Divisional application 97106464.7 filed on 18/04/97.

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 709 872 B1

Description

[0001] This invention relates to a cathode ray tube apparatus, and especially relates to a cathode ray tube apparatus having a shadow mask which is fixed on a frame under a condition that a predetermined tension is applied to the shadow mask.

[0002] In a flat type color cathode ray tube apparatus, about 80 % of electron beams which are emitted from electron guns collide with a shadow mask. The shadow mask is heated by the collision of the electron beams, and it is deformed by thermal expansion. In order to prevent the reduction of the quality of picture images displayed on a screen of the cathode ray tube apparatus caused by the deformation of the shadow mask, the shadow mask has been fixed on a frame under a condition that a predetermined tension is applied to the shadow mask in the conventional color cathode ray tube apparatus.

[0003] The frame of the conventional color cathode ray tube apparatus is integrally formed from a plate by press working in order to make a cross-sectional shape of each side substantially L-shaped. Alternatively, the frame is formed by welding of four angle bars having a substantially L-shaped cross-section in order to make each angle between the sides be substantially right angle. Therefore, an electron beam through hole on the frame is formed as a substantially rectangular shape. At the same time, the manufacturing process of the frame can be made simple and the cost of the frame can be reduced.

[0004] On the other hand, when the rigidity of the frame is not sufficient, the frame will be deformed by the tension applied to the shadow mask. Thereby, the surface of the shadow mask corrugates. Furthermore, the relative positions of electron beam through holes on the shadow mask against phosphor regions on the screen are discrepant. Thus, a mislanding occurs on the color cathode ray tube apparatus. For preventing the deformation of the frame according to the prior art portion of claims 1 and 15, as shown in JP-A-3-187132, the cross-sectional shape of each side of the frame is made to be substantially triangular for increasing the rigidity of the frame.

[0005] Furthermore, in the shadow mask which is fixed on the frame with the predetermined tension, the tension should be larger to cancel the thermal expansion of the shadow mask sufficiently, for preventing the mislanding due to the thermal expansion of the shadow mask, when the shadow mask is heated by the irradiation of the electron beams during operation of the color cathode ray tube apparatus. Therefore, the frame is made of a material having a larger thermal expansion coefficient than that of the material of the shadow mask, which is, for example, shown in JP-A-2-204943.

[0006] In the flat type color cathode ray tube apparatus, the aspect ratio is, for example, 3:4 or 9:16, so that the screen or the frame is horizontally oblong. Thus,

when the shadow mask is fixed on the frame by welding with the predetermined tension in the manufacturing process, quantities of the strain of the longer side and the shorter side are different from each other. Therefore, the tension which is applied to the shadow mask becomes uneven. As a result, the mislanding will occur due to the discrepancy between the electron beam through holes on the shadow mask and the phosphor regions on the screen by the thermal expansion of the shadow mask during operation of the color cathode ray tube apparatus.

[0007] Furthermore, since the tension along the longer side is larger, the longer sides of the frame warp inward. At the same time, the shorter sides warp outward. For preventing the interlocking of the warp of the longer sides and the shorter sides, it is proposed that cuttings are provided on respective corners of the frame for warping the longer sides and the shorter sides independently, which is, for example, shown in JP-A-5-290754. However, when the cross-section of each side of the frame is of triangular shape, a reinforcing plate is to be obliquely welded between a side wall perpendicular to the shadow mask face and a flange parallel to the shadow mask face. Alternatively, each side member of the frame is formed by bending a plate to provide a substantially triangular cross-section or formed by cutting a bar having a substantially triangular cross-section, and the side members are welded at four corners of the frame. By such a configuration, the frame has disadvantages in that the weight of the frame becomes heavier and the working process of the frame becomes complex, and the cost for manufacturing the frame becomes expensive. Furthermore, when the cuttings are provided on respective corners of the frame, the tension applied to the shadow mask will be uneven in the vicinity of the cuttings. Thus, the corrugation occurs in those parts, and the corrugation becomes the cause of the mislanding of the picture image displayed on the screen of the color cathode ray tube apparatus.

[0008] Furthermore, in a heat treatment during the manufacturing process of the color cathode ray tube apparatus, plastic deformation occurs in the shadow mask. Thus, the tension which is applied to the shadow mask is reduced. Generally, a temperature of the shadow mask in a normal actuation of the color cathode ray tube apparatus is about 100 degrees Celsius. On the other hand, the highest temperature of the shadow mask in the heat treatment is about 450 degrees Celsius. As mentioned above, the frame is made of the material having larger thermal expansion coefficient than that of the material of the shadow mask for preventing the reduction of the tension applied to the shadow mask. Since the temperature of the shadow mask and the frame in the heat treatment in the manufacturing process becomes about five times as large as the temperature in the normal operation of the cathode ray tube apparatus, the difference between the thermal expansion of the shadow mask and the thermal expansion of the frame

is magnified. Thus, the tension applied to the shadow mask will be larger than that in the normal actuation of the color cathode ray tube apparatus or the ordinary temperature. As a result, a plastic deformation occurs in the shadow mask. The tension applied to the shadow mask in which the plastic deformation occurs will be reduced at the ordinary temperature, and a mislanding will occur during operation of the color cathode ray tube apparatus.

[0009] An objective of this invention is to provide an improved color cathode ray tube apparatus, in which the tension applied to the shadow mask is uniform in each direction after the welding of the shadow mask on the frame. Another objective of this invention is to provide an improved cathode ray tube apparatus, in which no corrugation occurs on the shadow mask even when the shadow mask is welded on the frame with a predetermined tension, and the weight of the frame is not increased and the working process of the frame does not become complex. These objects are solved with the features of the claims.

[0010] For achieving the above-mentioned objectives, color cathode ray tube apparatuses of this invention commonly comprise a funnel, a panel, a phosphor screen disposed inside of the panel, a shadow mask disposed in the vicinity of the phosphor screen, a frame on which the shadow mask is fixed and an electron gun disposed in a neck part of the funnel. The frame has a shadow mask welding face which has a substantially rectangular shape, side walls which are continuously formed along an inner periphery of the shadow mask welding face and are substantially perpendicular to the shadow mask welding face and a flange face which is formed along the side walls and is substantially parallel to the shadow mask welding face. The shadow mask is fixed on the shadow mask welding face of the frame by welding under a condition that a predetermined tension is applied to the shadow mask. The mechanical strength of the longer sides of the frame is higher than that of the shorter sides of the frame. By such a configuration, quantities of the deformation along the longer sides and the shorter sides of the frame can be made equal to the quantities of the deformation of the shadow mask along the longer sides and the shorter sides. Thus, after the welding of the shadow mask on the frame, the tension applied to the shadow mask can be made even. Furthermore, the deformation of the frame is smaller, so that the tension applied to the shadow mask can be maintained in a predetermined value. Still furthermore, in a manufacturing process or normal actuation of the color cathode ray tube apparatus, even when the shadow mask and/or the frame are/is deformed by thermal expansion, an assembly in which the shadow mask is welded on the frame maintains a similar shape to that of the initial state. Thus, no corrugation occurs on the shadow mask face. As a result, the thermal expansion of the shadow mask can be cancelled or absorbed by the tension applied to the shadow mask. Positions of

electron beam through holes and phosphor regions on a phosphor screen of the color cathode ray tube apparatus are then relatively coincident with each other. The mislanding in a picture image displayed on the screen of the color cathode ray tube apparatus can be reduced.

[0011] By such a configuration according to the invention, the frame, in which the mechanical strength of the longer side is higher than that of the shorter side, can easily be obtained by applying the conventional frame.

[0012] Still furthermore, it is preferable that a width of at least a part of the flange face on each longer side of the frame is wider than a width of the flange face on each shorter side of the frame. Alternatively, it is preferable that the side wall on each longer side of the frame swells outward on a plane parallel to the shadow mask welding face. Alternatively, it is preferable that at least a part of the flange face on each shorter side of the frame is cut out. Alternatively, it is preferable that the flange face of each shorter side is warped in a manner so that a height of the lowest part of the shorter side of the frame is lower than the height of the longer side. By such a configuration, the frame, in which the mechanical strength of the longer side is higher than that of the shorter side, likewise can easily be obtained. In these cases, the frame can be formed integrally by press working, so that the configurations of the frame are suitable for mass production.

[0013] Furthermore, it is preferable that the longer sides and the shorter sides of the frame are respectively formed as independent members, and a thickness of a first member for the longer side is larger than that of a second member for the shorter side. Alternatively, it is preferable that the longer sides and the shorter sides of the frame are respectively formed as independent members, and a material of a first member for the longer side is different from that of a second member for the shorter side. By such a configuration, the frame, in which the mechanical strength of the longer side is higher than that of the shorter side, can be obtained. These configurations of the frame are suitable for a production of small quantity. In the latter case, it is especially preferable that Young's modulus of the material of the first member for the longer side is higher than that of the second member for the shorter side. Thereby, the thickness and the shape of the cross-section of the first member can be made the same as those of the second member. As a result, the assembly of the frame can be made easier without using any special jig.

[0014] Furthermore, it is preferable that a thermal expansion coefficient of a material of the frame is smaller than that of a material of the shadow mask. By such a configuration, it is possible to prevent the plastic deformation of the shadow mask due to the difference between the heat capacities of the frame and the shadow mask, when the funnel and the panel of the color cathode ray tube apparatus, which are made of glass, are connected.

[0015] In a further embodiment of a color cathode ray

tube apparatus of this invention,

[0016] the frame has a shadow mask welding face in which four sides thereof are continuously formed as substantially rectangular shape and side walls which are continuously formed along an inner periphery of the shadow mask welding face, and has alternately formed perpendicular portions and slanted portions, and a flange face which is formed along the side walls and is substantially parallel to the shadow mask welding face. The perpendicular portions are substantially perpendicular to the shadow mask welding face and the slanted portions are formed to be slanted to the inside of the frame. The shadow mask is fixed on the shadow mask welding face of the frame by welding under a condition that a predetermined tension is applied to the shadow mask. By such a configuration, the slanted portions of the side walls of the frame serve as ribs, so that the rigidity of the frame against the tension applied to the shadow mask can be made higher without increasing the weight. Thus, the deformation of the frame by the tension applied to the shadow mask can be prevented. Furthermore, respective sides of the shadow mask welding face are continued and no cuttings are formed at the corners, so that the tension applied to the shadow mask may not be uneven in the vicinity of the corners. No corrugation occurs in the vicinity of the corners.

[0017] In the above-mentioned configuration, it is preferable that the ridge lines of the slanted portions of the side walls are substantially parallel to the sides of the shadow mask welding face, and the slanted portion forms an opening having a substantially triangular shape on a plane perpendicular to the shadow mask welding face with the perpendicular portion of the side wall and the flange face. By such a configuration, the frame can be formed by press working.

[0018] Furthermore, it is preferable that at least one of the number and the dimension of the perpendicular portions and the slanted portions of the side walls on the longer sides is different from that on the shorter sides. By such a configuration, the mechanical strength of respective sides can be controlled responding to the length of the sides or the strength of the tension applied to the shadow mask.

[0019] In a still further embodiment of a color cathode ray tube apparatus of this invention the frame has a shadow mask welding face in which four sides thereof are continuously formed as substantially rectangular in shape and side walls which are continuously formed along an inner periphery of the shadow mask welding face, and has alternately formed perpendicular portions and first and second slanted portions, and a flange face which is formed along the side walls and is substantially parallel to the shadow mask welding face. The perpendicular portions are substantially perpendicular to the shadow mask welding face and the first slanted portions are formed to be slanted to the inside of the frame, and the second slanted portions are formed to be slanted to the outside of the frame. The shadow mask is fixed on

the shadow mask welding face of the frame by welding under a condition that a predetermined tension is applied to the shadow mask. In the above-mentioned configuration, it is preferable that the ridge lines of the side walls and the shadow mask welding face are straight lines, and the ridge lines of the side walls and the flange face are wave lines. By such a configuration, the frame can be formed by press working. Furthermore, the mechanical strength of the frame can be made entirely even on respective sides.

[0020] Furthermore, it is preferable that a cross-sectional shape of the side walls of the frame in the vicinity of the boundary between the shadow mask welding face and the side walls on a plane parallel to the shadow mask welding face is substantially octagonal. Furthermore, it is preferable that the frame is integrally formed by press working. By such a configuration, a gap is formed between the side walls and the shadow mask welding face in the vicinity of each corner of the frame. Thus, the shape of each corner of the shadow mask welding face can be made stable in the press working, and the flatness of the shadow mask welding face can be maintained. Furthermore, it is preferable that the thermal expansion coefficient of the material of the frame is smaller than that of the material of the shadow mask. By such a configuration, it is possible to prevent the plastic deformation of the shadow mask due to the difference between the heat capacities of the frame and the shadow mask, when the funnel and the panel of the color cathode ray tube apparatus, which are made of glass, are connected.

FIG.1 is a cross-sectional plan view showing a configuration of a first embodiment of a color cathode ray tube apparatus of this invention;

FIG.2 is a perspective view showing a configuration of a frame in the first embodiment;

FIG.3 is a perspective view showing another configuration of the frame in the first embodiment;

FIG.4 is a perspective view showing still another configuration of the frame in the first embodiment;

FIG.5 is a perspective view showing a configuration of a frame in an embodiment of a color cathode ray tube apparatus not forming part of this invention;

FIG.6 is a perspective view showing another configuration of the frame in the embodiment of figure 5;

FIG.7 is a perspective view showing still another configuration of the frame in the embodiment of figure 5;

FIG.8 is a perspective view showing still another configuration of the frame in the embodiment of figure 5;

FIG.9 is a perspective view showing a configuration of a frame in an embodiment of a color cathode ray tube apparatus not forming part of this invention;

FIG.10 is a perspective view showing another configuration of the frame in the embodiment of figure 9;

FIG.11 is a cross-sectional plan view showing a

configuration of an embodiment of a color cathode ray tube apparatus of this invention;

FIG.12 is a perspective view showing a configuration of a frame in the embodiment of figure 11;

FIG.13 is a perspective view showing a configuration of a frame in an embodiment of a color cathode ray tube apparatus of this invention;

FIGs. 14(a), 14(b) and 14(c) are respectively cross-sectional side views showing configurations of the frame along A-A, B-B and C-C lines;

FIG.15 is a perspective view showing a configuration of a frame in an embodiment of a color cathode ray tube apparatus not forming part of this invention;

FIG.16 is a drawing showing the temperature rise of a shadow mask during normal operation of the color cathode ray tube apparatus;

FIG.17 is a drawing showing a characteristic curve of the reduction of a tension applied to the shadow mask; and

FIG.18 is a drawing showing characteristic curves of the thermal expansion of the shadow mask and the frame.

[0021] A first embodiment of a color cathode ray tube apparatus of this invention is described referring to FIGs. 1 to 4. As can be seen from FIG.1, the first embodiment of the color cathode ray tube apparatus of this invention comprises a funnel 1 made of glass, a panel 2 made of glass, a phosphor screen 8 disposed inside of the panel 2, a shadow mask 3 disposed in the vicinity of the phosphor screen 8, a frame 4 for supporting the shadow mask 3, and an electron gun 6 disposed in a neck part of the funnel 1. The shadow mask 3 is fixed on the frame 4 by resistance welding, laser welding working, and the like under a condition that a predetermined tension of about 10 Kg/mm² is applied to the shadow mask 3. The longer sides of the frame are about 333 mm, and the shorter sides are about 256 mm. The cross-sectional shapes of the respective sides are substantially L-shaped.

[0022] Electron beams, which correspond to red, green and blue colors and are radiated from the electron gun 6, pass through predetermined electron beam through holes formed on the shadow mask and reach predetermined phosphor regions of the phosphor screen 8 corresponding to the colors of the electron beams. Each phosphor region, which is irradiated by the electron beam, luminesces the color of red, green or blue corresponding to the electron beam. Thus, a color picture image can be displayed on the screen of the panel 2 of the color cathode ray tube apparatus.

[0023] As can be seen from FIG.2, the frame 4 has a substantially rectangular shape viewed on a plane parallel to the shadow mask 3. A shadow mask welding face 41, which is parallel to the shadow mask 3, is formed at an open end of the frame 4. Flange faces 43a and 43b, which are parallel to the shadow mask welding face 41, are formed at the other open end of the frame 4. Side

walls 42a and 42b are integrally formed along the inner peripheries of longer sides 41a and shorter sides 41b of the shadow mask welding face 41. Furthermore, the side walls 42a and 42b and the flange faces 43a and 43b are respectively formed integrally. Reinforcing plates 44 are respectively fixed on the flange faces 43a on the longer sides.

[0024] The frame 4 shown in FIG.2 can be obtained by fixing the reinforcing plates 44 by spot welding and the like on a frame which is conventionally used and is integrally formed by press working. As mentioned above, when the reinforcing plates 44 are provided on the flange faces 43a on the longer sides of the frame 4, a frame, in which the mechanical strength of the longer sides is higher than that of the shorter sides, can easily be obtained. Alternatively, as shown in FIG.3, substantially rectangular plates 45, which are obliquely fixed between the side walls 42a and the flange faces 43a on the longer sides, can be used as reinforcing plates. Thereby, the mechanical strength of the longer sides can be made higher than that of the shorter sides. Alternatively, as shown in FIG.4, substantially triangle plates 46, which are fixed between the side walls 42a and the flanges 43a on the longer sides at a predetermined intervals and oriented to be perpendicular to the shadow mask 3, can be used as reinforcing plates. Thereby, the mechanical strength of the longer sides similarly can be made higher than that of the shorter sides.

[0025] For discussion, the length of the longer sides (41a, 42a, 43a) of the frame 4 will be called L1, the length of the shorter sides (41b, 42b, 43b) of the frame 4 L2, Young's modulus of the shadow mask 3 along the longer side E1, Young's modulus of the shadow mask 3 along the shorter sides E2, a tension applied to the shadow mask 3 in a direction parallel to the longer sides T1, a tension applied to the shadow mask 3 in a direction parallel to the shorter sides T2, a rigidity of the longer sides of the frame 4 G1, and a rigidity of the shorter sides of the frame 4 G2. When the material and the shape of the frame 4 satisfy the equation of

$$\frac{L2 \cdot E1 \cdot T1}{L1 \cdot E2 \cdot T2} = \frac{G1}{G2},$$

quantities of the deformation of the longer sides and the shorter sides of the frame 4 can be made the same as those of the shadow mask 3. Thus, even when the shadow mask 3 is welded on the frame 4, the tension applied to the shadow mask 3 can be made even in each direction. As a result, the position of each electron beam through hole formed on the shadow mask 3 and the position of the phosphor region corresponding to the electron beam through hole can coincide with each other. Mislanding of the picture image on the screen can be prevented substantially perfectly.

[0026] As a material of the shadow mask 3, iron was used. As a material of the frame 4, an alloy selected from

13%Cr-Fe, 18%Cr-Fe, 50%Ni-Fe and 42%Ni-Fe, which have a thermal expansion coefficient smaller than that of the soft steel, was used.

[0027] When the funnel 1 and the panel 2 were connected, the frame 4 and the shadow mask 3 were exposed to a high temperature at the circumference for a long time. However, the thermal expansion of the frame 4 was smaller than that of the shadow mask 3. Thus, the material of the shadow mask did not surpass the elastic limit, and no plastic deformation has occurred in the shadow mask 3.

[0028] By the above-mentioned configuration, the mechanical strength of the longer sides of the frame 4 could be made higher than that of the shorter sides of the frame 4. Thus, even when the stress on the longer sides due to the tension of the shadow mask 3 was larger than that of the shorter sides, the quantity of the deformation of the longer sides of the frame 4 could be made smaller. As a result, quantities of the deformation of the longer sides and the shorter sides of the frame 4 could be made the same as those of the shadow mask 3. Thus, after the welding of the shadow mask 3 on the frame 4, the tension applied to the shadow mask 3 could be made even in each direction. Furthermore, since the deformation of the frame 4 was smaller, the predetermined tension of the shadow mask 3 could be obtained. Thus, the thermal expansion of the shadow mask 3 could be cancelled or absorbed by the tension applied to the shadow mask 3. The relative position of each electron beam through hole on the shadow mask 3 could coincide with the position of the phosphor region corresponding to the electron beam through hole. The mislanding of the picture image displayed on the screen was not observed.

[0029] In the first embodiment, the reinforcing plates 44, 45 or 46 are provided only on the longer sides of the frame 4. However, it is possible to provide the reinforcing member on not only the longer sides but also the shorter sides of the frame 4. In such a case, at least one of the shape, thickness, number and material of the reinforcing member on the longer sides is different from that of the reinforcing member on the shorter sides. Thereby, the mechanical strength of the longer sides of the frame 4 can be higher than that of the shorter sides. Furthermore, it is possible that the reinforcing plates 44, 45 or 46 are used in combination with other kinds of the reinforcing plates in the remainder. The same effects can be obtained in the latter case.

[0030] An embodiment of a color cathode ray tube apparatus not forming part of this invention is described referring to FIGs. 5 to 8. The configuration of this embodiment of the color cathode ray tube apparatus is substantially the same as that of the first embodiment shown in FIG.1. However, only the shape of the frame 4 in this embodiment is different from that in the first embodiment. Thus, the explanation of the duplicated configuration of the color cathode ray tube apparatus is omitted.

[0031] As can be seen from FIG.5, the frame 4 has a substantially rectangular shape on a plane parallel to the shadow mask 3 (not shown in FIG.5). A shadow mask welding face 41, which is parallel to the shadow mask 3, is formed at an open end of the frame 4. Flange faces 43a and 43b, which are parallel to the shadow mask welding face 41, are formed at the other open end of the frame 4. Side walls 42a and 42b are integrally formed along inner peripheries of longer sides 41a and shorter sides 41b of the shadow mask welding face 41. Furthermore, the side walls 42a and 42b and the flange faces 43a and 43b are respectively formed integrally. Herein, a width W1 of the flange face 43a on the longer sides is wider than a width W2 of the flange face 43b on the shorter sides.

[0032] Alternatively, as shown in FIG.6, it is possible that the side walls 42a on the longer sides are protruded outwardly. By such a configuration, the width W1 of the flange face 43a on the longer sides can be partially wider than the width w2 of the flange face 43b on the shorter sides. Alternatively, as shown in FIG.7, it is possible to cut a part of the flange face 43b. By such a configuration, the width W1 of the flange face 43a on the longer sides can be relatively wider than the width w2 of the flange face 43b on the shorter sides. Namely, when the width W1 of at least a part of the flange face 43a on the longer sides of the frame is made wider than the width W2 of the flange face 43b on the shorter sides, a frame in which the mechanical strength of the longer sides is higher than that of the shorter sides can be obtained. Alternatively, as shown in FIG.8, it is possible that the height H2 of at least a part of the side walls 42b on the shorter sides of the frame 4 is smaller than the height H1 of the side walls 41a on the longer sides. Thereby, a frame in which the mechanical strength of the longer sides is higher than that of the shorter sides can be obtained. In these cases, the frame 4 can be formed integrally by press working, so that the configuration of the frame 4 is suitable for mass production. Furthermore, each feature of the embodiment shown in one of FIGs. 5 to 8 can be applied in combination with other features in the remainder. Thereby, a frame in which the mechanical strength of the longer side is higher than that of the shorter sides can be obtained. Still furthermore, it is possible that each feature of this embodiment can be combined with at least one feature of the first embodiment shown in FIGs. 2 to 4.

[0033] Next, an embodiment of a color cathode ray tube apparatus not forming part of this invention is described referring to FIGs. 9 and 10. The configuration of this embodiment of the color cathode ray tube apparatus is substantially the same as that of the first embodiment shown in FIG.1. However, only the shape of the frame 4 in this embodiment is different from that in the first embodiment. Thus, the explanation of the duplicated configuration of the color cathode ray tube apparatus is omitted.

[0034] As can be seen from FIG.9, the longer sides

and the shorter sides of the frame 4 are respectively formed as independent members 4a and 4b. The thickness of the longer side member 4a is larger than that of the shorter side member 4b. Since the material of the longer side member 4a is essentially the same as that of the shorter side member 4b, the frame 4 can be assembled by welding. By such a configuration, a frame in which the mechanical strength of the longer side is higher than that of the shorter sides can be obtained. Alternatively, it is possible that the material of the longer side member 4a is different from that of the shorter side member 4b. In this case, a material having Young's modulus larger than that of the material of the shorter side member 4b can be used as the material of the longer side member 4a. Thereby, the thickness and the cross-sectional shape of the longer side member 4a can be made the same as those of the shorter side member 4b. In the former case shown in FIG.9, a special jig for adjusting the difference between the thickness of the longer side member 4a and the thickness of the shorter side member 4b is necessary. However, in the latter case shown in FIG.10, since the thickness of the longer side member 4a can be made the same as that of the shorter side member 4b, the special jig for adjusting the difference between the thicknesses is not necessary. Thereby, the difficulty of the welding due to the difference of the materials of the longer side member 4a and the shorter side member 4b in the latter case can be reduced. As the combination of the materials of the longer side member 4a and the shorter side member 4b, an alloy including aluminum and stainless steel or normal steel, and stainless steels having different components can be used. This embodiment is suitable for a production of small quantity.

[0035] Next, an embodiment of a color cathode ray tube apparatus of this invention is described referring to FIGs. 11 and 12. As can be seen from FIG.11, the configuration of this embodiment of the color cathode ray tube apparatus is substantially the same as that of the first embodiment shown in FIG.1 except the shape of the frame 4. Thus, the detailed explanation of the configuration of this embodiment of the color cathode ray tube apparatus is omitted.

[0036] As can be seen from FIG.12, the frame 4 has a substantially rectangular in cross-section viewed on a plane parallel to the shadow mask 3 (not shown in FIG. 12). A shadow mask welding face 41, which is parallel to the shadow mask 3 and on which the shadow mask 3 is to be welded, is formed at an open end of the frame 4. A flange face 43, which is parallel to the shadow mask 3, is formed at the other open end of the frame 4. The shadow mask welding face 41 is a substantially rectangular shape, in which respective longer sides 41a and shorter sides 41b are integrally formed. No cutting is formed at each corner. Side walls 42 are integrally formed along inner peripheries of the sides 41a and 41b of the shadow mask welding face 41. Perpendicular portions 142a which are perpendicular to the shadow mask

welding face 41 and slanted portions 142b which are slanted inside of the frame 4 are alternately formed on the side walls 42. Furthermore, the side walls 42 and the flange face 43 are integrally formed.

[0037] Namely, the frame shown in FIG.12 is formed integrally by press working. For making the press working easy, the ridge lines at the top of the slanted portions 142b on the side walls 42 are substantially parallel to the sides 41a or 41b of the shadow mask welding face 41. On a plane perpendicular to the shadow mask 3, a substantially triangular opening 142d is formed by the perpendicular portion 142a and the slanted portion 142b of the side walls 42 and the flange face 43. Furthermore, the cross-sectional shape of the side walls 42 on a plane parallel to and in the vicinity of the shadow mask welding face 41 is substantially octagonal. By such a configuration, a gap 41d can be formed between each corner 41c of the shadow mask welding face 41 and the side walls 42. Thus, the shape of each corner 41c of the shadow mask welding face 41 can be stable in the press working, and the flatness of the shadow mask welding face 41 can be maintained.

[0038] Responding to the length of the longer sides 41a and the shorter sides 41b and the tension applied to the shadow mask 3, at least one of dimension and number of the perpendicular portions 142a and the slanted portions 142b is varied. In this embodiment, the width of the perpendicular portions 142a and the number of the slanted portions 142b are varied.

[0039] By the above-mentioned configuration, the slanted portions 142b which are formed on the side walls 42 and slanted to the inside of the frame 4 serve as ribs. Thus, the rigidity of the frame 4 against the tension applied to the shadow mask 3 can be made higher, without increasing the weight of the frame 4. The deformation of the frame 4 due to the tension applied to the shadow mask 3 can be prevented. Furthermore, the longer side 41a and the shorter side 41b are continuously formed at each corner of the shadow mask welding face 41, and no cutting is formed at the corner of the shadow mask welding face 41. The tension applied to the shadow mask 3 may not be uneven in the vicinity of the corners of the shadow mask welding face 41, so that no corrugation occurs in the vicinity of the corners.

[0040] Next, an embodiment of a color cathode ray tube apparatus of this invention is described referring to FIGs. 13, 14(a), 14(b) and 14(c). The configuration of this embodiment of the color cathode ray tube apparatus is substantially the same as the configuration of the embodiments shown in FIG. 1 or 11, except for the shape of the frame 4. Thus, the duplicating description of the configuration of this embodiment of the color cathode ray tube apparatus is omitted.

[0041] As can be seen from FIG.13, the frame 4 in this embodiment is substantially rectangular in cross-section viewed on a plane parallel to the shadow mask 3 (not shown in FIG.13). A shadow mask welding face 41, which is parallel to the shadow mask 3 and on which the

shadow mask 3 is to be welded, is formed at an open end of the frame 4. A flange face 43, which is parallel to the shadow mask 3, is formed at the other open end of the frame 4. The shadow mask welding face 41 is of substantially rectangular shape, in which respective longer sides 41a and shorter sides 41b are integrally formed. No cutting is formed at each corner. Side walls 145 are integrally formed along inner peripheries of the sides 41a and 41b of the shadow mask welding face 41.

[0042] The side walls 145 are formed by alternation of a first slanted portion 45a shown in FIG.14(a), a perpendicular portion 45b shown in FIG.14(b) and a second slanted portion 45c shown in FIG.14(c). The first slanted portion 45a is slanted to the inside of the frame 4 along line A-A in FIG.13. The perpendicular portion 45b is perpendicular to the shadow mask welding face 41 along line B-B in FIG.13. The second slanted portion 45c is slanted to the outside of the frame 4 along line C-C in FIG.13. Furthermore, the side walls 42 and the flange face 43 are integrally formed. The ridge lines between the shadow mask welding face 41 and the side walls 145 are respectively straight lines. However, the ridge lines between the flange face 43 and the side walls 145 are wave forms.

[0043] Similar to the above-mentioned embodiment of this invention shown in figures 11 and 12, the cross-sectional shape of the side walls 145 on a plane parallel to and in the vicinity of the shadow mask welding face 41 is substantially octagonal. By such a configuration, a gap 41d can be formed between each corner 41c of the shadow mask welding face 41 and the side walls 145. Thus, the shape of each corner 41c of the shadow mask welding face 41 can be stable in the press working, and the flatness of the shadow mask welding face 41 can be maintained.

[0044] By the above-mentioned configuration, the first and the second slanted portions 45a and 45c, which are formed on the side walls 145 of the frame 4, serve as ribs. Thus, the rigidity of the frame 4 against the tension applied to the shadow mask 3 can be made higher, without increasing the weight of the frame 4. The deformation of the frame 4 due to the tension applied to the shadow mask 3 can be prevented. Furthermore, the longer side 41a and the shorter side 41b are continuously formed at each corner of the shadow mask welding face 41, and no cutting is formed at the corner of the shadow mask welding face 41. The tension applied to the shadow mask 3 may not be uneven in the vicinity of the corners of the shadow mask welding face 41, so that no corrugation occurs in the vicinity of the corners.

[0045] In the above-mentioned embodiments of this invention shown in figures 11-14, as a material of the shadow mask 3, iron was used. As a material of the frame 4, an alloy selected from 13%Cr-Fe, 18%Cr-Fe, 50%Ni-Fe and 42%Ni-Fe, which have a thermal expansion coefficient smaller than that of the soft steel, was used. When the funnel 1 and the panel 2 were connected, the frame 4 and the shadow mask 3 were exposed

to a high temperature at the circumference for a long time. However, the thermal expansion of the frame 4 was smaller than that of the shadow mask 3. Thus, the material of the shadow mask did not surpass the elastic limit, and no plastic deformation occurred in the shadow mask 3.

[0046] Next, an embodiment of a color cathode ray tube apparatus not forming part of this invention is described referring to FIGs. 15 to 18. The configuration of this embodiment of the color cathode ray tube apparatus is substantially the same as the configuration of the embodiments shown in FIG. 1 or 11, except for the shape of the frame 4. Thus, the duplicating description of the configuration of this embodiment of the color cathode ray tube apparatus is omitted.

[0047] As can be seen from FIG.15, a shadow mask 3, which is made of an iron and has electron beam through holes arranged in a pitch of about 0.26 mm, is fixed on a frame 4 with a tension for cancelling or absorbing thermal expansion of the shadow mask 3 during normal operation of the color cathode ray tube apparatus. The frame 4 is made of an alloy containing 50%Ni and Fe. A slit 41d is formed at each corner 41c of a shadow mask welding face 41 for providing an elasticity to the frame 4. Under a condition that side walls 42 of the frame 4 are warped to the inside of the frame 4, the shadow mask 3 is welded on the shadow mask welding face 41. Thereby, a predetermined tension can be applied to the shadow mask 3.

[0048] When the shadow mask 3 is made of iron, the thermal expansion coefficient α_M is 12×10^{-6} ($1/^\circ\text{C}$) and Young's modulus E_M is 9800 kg/mm². When the room temperature is 20 degrees Celsius, the temperature rise of the shadow mask during the normal operation of the color cathode ray tube apparatus will be about 80 degrees Celsius. The tension T for cancelling or absorbing the thermal expansion of the shadow mask during the normal operation is obtained by the equation of

$$T \geq \alpha_M \cdot \Delta t_o \cdot E_M.$$

Actually, T is over 9.4 kg/mm².

[0049] A relation between the tension applied to the shadow mask 3 and the reduction of the tension after a heat treatment is shown in FIG.17. When a conventional color cathode ray tube apparatus was produced with a shadow mask assembly, in which the shadow mask 3 made of iron was fixed on a frame 4 made of the same iron with a tension of 9.4 kg/mm², the tension applied to the shadow mask 3 was reduced by about 70 to 80 % after the heat treatment in a temperature of about 450 degree Celsius. The reason the tension applied to the shadow mask 3 was reduced was the plastic deformation of the shadow mask.

[0050] As can be seen from FIG.17, it is preferable that the tension applied to the shadow mask 3 is zero for preventing the reduction of the tension applied to the

shadow mask 3 due to the heat treatment. However, it is necessary that the tension applied to the shadow mask 3 in the assembly of the shadow mask assembly is 9.4 kg/mm². Thus, it is impossible to make the tension applied to the shadow mask 3 zero.

[0051] Therefore, a shadow mask assembly, in which the tension applied to the shadow mask 3 is zero at the temperature of 450 degrees Celsius in the heat treatment and the tension cancelling the thermal expansion can be applied to the shadow mask 3 during the normal operation of the color cathode ray tube apparatus, is necessary. For obtaining such a shadow mask assembly, a thermal expansion coefficient α_F of the frame 4, in which the characteristic curve A of the thermal expansion of the shadow mask 3 and the characteristic curve B of the frame 4 cross at 450 degrees Celsius, is obtained from FIG.18. A relation between the thermal expansion coefficient α_F of the frame 4, by which the tension applied to the shadow mask 3 becomes zero at 450 degrees Celsius, and the thermal expansion coefficient α_M of the shadow mask 3 is shown by the equation of

$$\alpha_F \leq \alpha_M (1 - (\Delta t_o / \Delta t)).$$

Herein, the temperature rise of the shadow mask 3 during the normal operation of the color cathode ray tube apparatus is Δt (°C) and the temperature rise of the shadow mask 3 in the heat treatment during the producing process of the color cathode ray tube apparatus is Δt_o (°C). The thermal expansion coefficient can be decided by the above-mentioned equation.

[0052] When the shadow mask 3 is made of iron, the thermal expansion coefficient of the frame α_F is obtained by

$$\alpha_F \leq 12 \times 10^{-6} \times (1 - (80/430)).$$

Namely, the value of the thermal expansion coefficient of the frame 4 is to be smaller than 9.7×10^{-6} (1/°C). A material having a thermal expansion coefficient similar to the above-mentioned value is 50%Ni-Fe alloy. By such a configuration, the plastic deformation of the shadow mask in the heat treatment can be prevented. Thus, the reduction of the tension applied to the shadow mask 3 due to the plastic deformation of the shadow mask 3 can be prevented.

Claims

1. A color cathode ray tube apparatus comprising a funnel (1), a panel (2), a phosphor screen (8) disposed inside of said panel (2), a shadow mask (3) disposed in the vicinity of said phosphor screen (8), a frame (4) on which said shadow mask (3) is fixed and an electron gun (6) disposed in a neck part of

said funnel (1); said frame (4) having a shadow mask welding face (41) which has a substantially rectangular shape defined by opposed pairs of longer and shorter sides, side walls (42a, 42b) which are continuously formed along an inner periphery of said shadow mask welding face (41) and are substantially perpendicular to said shadow mask welding face (41), and a flange face (43a, 43b) which is formed along said side walls (42a, 42b) and is substantially parallel to said shadow mask welding face (41), characterized by that

said shadow mask (3) is fixed on said shadow mask welding face (41) of said frame (4) by welding under a condition that a predetermined tension is applied to said shadow mask (3); and

at least one reinforcing member (44;45;46) is provided on said flange face (43a) each of the longer sides (43a) of said frame (4) so that a mechanical strength of the longer sides (42a, 43a) of said frame (4) is higher than that of the shorter sides (42b, 43b) of said frame.

2. The apparatus in accordance with claim 1, wherein said reinforcing member (45) has a rectangular shape and is obliquely mounted between said side wall (42a) and said flange face (43a) of said frame (4).
3. The apparatus in accordance with claim 1 or 2, wherein another reinforcing member is further provided on each of the longer and shorter sides of said frame, but at least one of shape, thickness, and material of said reinforcing members provided on the longer sides is different from that of said reinforcing members provided on the shorter sides.
4. The apparatus according to claim 1, wherein said reinforcing member (46) has a substantially triangle shape and is mounted is between said side wall (42a) and said flange face (43a) and oriented substantially perpendicular to said shadow mask welding face (41).
5. The apparatus in accordance with claim 4, wherein at least one other reinforcing member (44;45;46) is further provided on each of the longer sides and shorter sides of said frame, but at least one of shape, thickness, number and material of said reinforcing members provided on the longer sides is different from that of said reinforcing members provided on the shorter sides.
6. The apparatus in accordance with any one of claims 1 to 5 wherein a width (W1) of at least a part of said flange face (43a) on each longer side of said frame (4) is wider than a width (W2) of said flange face (43b) on each shorter side of said frame (4).

7. The apparatus in accordance with any one of claims 1 to 6 wherein said side wall (42a) on each longer side of said frame (4) swells outward.
 8. The apparatus in accordance with any one of claims 1 to 7 wherein at least a part of said flange face (43b) on each shorter side of said frame (4) is cut out.
 9. The apparatus in accordance with any one of claims 1 to 8 wherein said flange face (43b) on each shorter side of said frame (4) is warped in a manner so that a height (H2) at the lowest part of the side wall (42b) on each shorter side of said frame (4) is lower than a height (H1) of the side wall (42a) on each longer side.
 10. The apparatus in accordance with any one of claims 1 to 9 wherein said longer sides (42a,43a) and said shorter sides (43a,43b) of said frame (4) are respectively formed from independent first and second members (4a,4b), and a thickness of the first member (4a) for said longer side is larger than that of the second member (4b) for said shorter side.
 11. The apparatus in accordance with any one of claims 1 to 9 wherein said longer sides (42a,43a) and said shorter sides (42b,43b) of said frame (4) are respectively formed from independent first and second members (4a,4b), and a material of the first member (4a) for said longer side is different from that of the second member (4b) for said shorter side.
 12. The apparatus in accordance with claim 11 wherein the Young's modulus of said material of said first member (4a) for said longer side is higher than that of said second member (4b) for said shorter side.
 13. The apparatus in accordance with claim 12, wherein said thickness and the shape of the cross-section of said first member (4a) are the same as those of said second member (4b).
 14. The apparatus in accordance with one of claims 1 to 13, wherein a thermal expansion coefficient of a material of said frame (4) is smaller than that of a material of said shadow mask (3).
 15. A color cathode ray tube apparatus comprising a funnel (1), a panel (2), a phosphor screen (8) disposed inside of said panel (2), a shadow mask (3) disposed in the vicinity of said phosphor screen (8), a frame (4) on which said shadow mask (3) is fixed and an electron gun (6) disposed in a neck part of said funnel (1);
- said frame (4) has a shadow mask welding face
- (41) in which four sides thereof are continuously formed in a substantially rectangular shape defined by opposed pairs of longer and shorter sides, side walls (42a,42b;145) which are continuously formed along an inner periphery of said shadow mask welding face (41) and a flange face (43;43a,43b) which is formed along said side walls (42a,42b;145) and is substantially parallel to said shadow mask welding face (41), characterized by that said side walls have alternately formed perpendicular portions (142a;45b) and slanted portions (142b;45a;45c), and said perpendicular portions (45b;142a) are substantially perpendicular to said shadow mask welding face (41) and said slanted portions (45a;142b) are formed to be slanted toward the inside of said frame (4); and said shadow mask (3) is fixed on said shadow mask welding face (41) of said frame (4) by welding under a condition that a predetermined tension is applied to said shadow mask (3).
 16. The apparatus in accordance with claim 15, wherein ridge lines (142c) of said slanted portions (142b) of said side walls (42) are substantially parallel to the sides of said shadow mask welding face (41), and said slanted portion (142b), said perpendicular portion (142a) of said side wall (42) and said flange face (43) define an opening having a substantially triangular shape on a plane perpendicular to said shadow mask welding face (41).
 17. The apparatus in accordance with claim 15 or 16, wherein at least one of the number and dimension of said perpendicular portion (142a) and said slanted portion (142b) of said side walls (42) on said longer sides is different from that on said shorter sides.
 18. The apparatus in accordance with claim 15, 16 or 17, wherein a cross-sectional shape of said side walls (42) of said frame (4) in the vicinity of a boundary between said shadow mask welding face (41) and said side walls (42) on a plane parallel to said shadow mask welding face (41) is substantially octagonal.
 19. The apparatus in accordance with any one of claims 15 to 18 wherein said frame (4) is integrally formed by press working.
 20. The apparatus in accordance with claim 15, wherein first and second slanted portions (45a,45c) are provided and said second slanted portions (45c) are formed to be slanted to the outside of said frame (4).
 21. The apparatus in accordance with claim 20, where-

in ridge lines (145a) of said side walls (145) and said shadow mask welding face (41) are straight lines, and ridge lines (145b) of said side walls (145) and said flange face (43) are substantially alternating sign wave forms.

22. The apparatus in accordance with claim 20 or 21, wherein a cross-sectional shape of said side walls (145) of said frame (4) in the vicinity of a boundary between said shadow mask welding face (41) and said side walls (145) on a plane parallel to said shadow mask welding face (41) is substantially octagonal.
23. The apparatus in accordance with claim 20, 21, or 22 wherein said frame (4) is integrally formed by press working.
24. The apparatus in accordance with any one of claims 15 to 23 wherein a thermal expansion coefficient of a material of said frame (4) is smaller than that of a material of said shadow mask (3).

Patentansprüche

1. Farbkathodenstrahlröhrenvorrichtung mit einem Trichter (1), einer Platte (2), einem innerhalb der Platte (2) angeordneten Phosphorschirm (8), einer in der Nähe des Phosphorschirms (8) angeordneten Schattenmaske (3), einem Rahmen (4), auf welchem die Schattenmaske (3) befestigt ist, und einer in einem Halsteil des Trichters (1) angeordneten Elektronenkanone (6); wobei der Rahmen (4) eine Schattenmasken-Anschweißfläche (41), welche eine im wesentlichen rechteckige Form gebildet durch gegenüberliegende Paare längerer und kürzerer Seiten besitzt, Seitenwände (42a, 42b), welche zusammenhängend entlang einem Innenumfang der Schattenmasken-Anschweißfläche (41) ausgebildet und im wesentlichen senkrecht zu der Schattenmasken-Anschweißfläche (41) angeordnet sind, und eine Flanschfläche (43a, 43b), welche entlang den Seitenwänden (42a, 42b) ausgebildet ist, und im wesentlichen parallel zu der Schattenmasken-Anschweißfläche (41) verläuft, aufweist, dadurch gekennzeichnet, daß

die Schattenmaske (3) auf der Schattenmasken-Anschweißfläche (41) durch Schweißen in einem Zustand befestigt ist, daß eine vorbestimmte Spannung auf die Schattenmaske (3) ausgeübt wird; und
wenigstens ein Verstärkungselement (44; 45; 46) an der Flanschfläche (43a) jeder längeren Seite (43a) des Rahmens (4) vorgesehen ist, so daß eine mechanische Festigkeit der längeren Seiten (42a, 43a) des Rahmens (4) höher

als die der kürzeren Seiten (42b, 43b) des Rahmens ist.

2. Vorrichtung nach Anspruch 1, wobei das Verstärkungselement (45) eine rechteckige Form aufweist und schräg zwischen der Seitenwand (42a) und der Flanschfläche (43a) des Rahmens (4) befestigt ist.
3. Vorrichtung nach Anspruch 1 oder 2, wobei ein weiteres Verstärkungselement ferner an jeder längeren und kürzeren Seite des Rahmens vorgesehen ist, aber wenigstens eines von Form, Dicke und Material der an den längeren Seiten vorgesehenen Verstärkungselemente sich von dem der an den kürzeren Seiten vorgesehenen Verstärkungselemente unterscheidet.
4. Vorrichtung nach Anspruch 1, wobei das Verstärkungselement (46) eine im wesentlichen dreieckige Form aufweist und zwischen der Seitenwand (42a) und der Flanschfläche (43a) befestigt und im wesentlichen senkrecht zu der Schattenmasken-Anschweißfläche (41) angeordnet ist.
5. Vorrichtung nach Anspruch 4, wobei wenigstens ein weiteres Verstärkungselement (44; 45; 46) ferner an jeder längeren und kürzeren Seite des Rahmens vorgesehen ist, aber wenigstens eines von Form, Dicke und Material der an den längeren Seiten vorgesehenen Verstärkungselemente sich von dem der an den kürzeren Seiten vorgesehenen kürzeren Seiten unterscheidet.
6. Vorrichtung nach einem der Ansprüche 1 bis 5, wobei eine Breite (W1) wenigstens eines Teils der Flanschfläche (43a) an jeder längeren Seite des Rahmens (4) breiter als eine Breite (W2) der Flanschfläche (43b) an jeder kürzeren Seite des Rahmens (4) ist.
7. Vorrichtung nach einem der Ansprüche 1 bis 6, wobei sich die Seitenwand (42a) an jeder längeren Seite des Rahmens (4) nach außen wölbt.
8. Vorrichtung nach einem der Ansprüche 1 bis 7, wobei wenigstens ein Teil der Flanschfläche (43b) an jeder kürzeren Seite des Rahmens (4) ausgeschnitten ist.
9. Vorrichtung nach einem der Ansprüche 1 bis 8, wobei die Flanschfläche (43b) an jeder kürzeren Seite des Rahmens (4) in einer Weise gewölbt ist, so daß eine Höhe (H2) an dem niedrigsten Teil der Seitenwand (42b) an jeder kürzeren Seite des Rahmens (4) niedriger als eine Höhe (H1) der Seitenwand (42a) an jeder längeren Seite ist.
10. Vorrichtung nach einem der Ansprüche 1 bis 9, wo-

bei die längeren Seiten (42a, 43a) und die kürzeren Seiten (43a, 43b) des Rahmens (4) jeweils aus unabhängigen ersten und zweiten Elementen (4a, 4b) ausgebildet sind, und eine Dicke des ersten Elements (4a) für die längere Seite größer als die des zweiten Elements (4b) für die kürzere Seite ist.

11. Vorrichtung nach einem der Ansprüche 1 bis 9, wobei die längeren Seiten (42a, 43a) und die kürzeren Seiten (42b, 43b) des Rahmens (4) jeweils aus unabhängigen ersten und zweiten Elementen (4a, 4b) ausgebildet sind, und ein Material des ersten Elements (4a) für die längere Seite sich von dem des zweiten Elements (4b) für die kürzere Seite unterscheidet.

12. Vorrichtung nach Anspruch 11, wobei der Elastizitätsmodul des Materials des ersten Elements (4a) für die längere Seite höher als der des zweiten Elements (4b) für die kürzere Seite ist.

13. Vorrichtung nach Anspruch 12, wobei die Dicke und die Querschnittsform des ersten Elements (4a) dieselben wie die des zweiten Elements (4b) sind.

14. Vorrichtung nach einem der Ansprüche 1 bis 13, wobei ein Wärmeausdehnungskoeffizient eines Materials des Rahmens (4) kleiner als der eines Materials der Schattenmaske (3) ist.

15. Farbkathodenstrahlröhrenvorrichtung mit einem Trichter (1), einer Platte (2), einem innerhalb der Platte (2) angeordneten Phosphorschirm (8), einer in der Nähe des Phosphorschirms (8) angeordneten Schattenmaske (3), einem Rahmen (4), auf welchem die Schattenmaske (3) befestigt ist, und einer in einem Halsteil des Trichters (1) angeordneten Elektronenkanone (6); wobei der Rahmen (4) eine Schattenmasken-Anschweißfläche (41), in welcher deren vier Seiten zusammenhängend in einer im wesentlichen rechteckigen Form, definiert durch gegenüberliegende Paare längerer und kürzerer Seiten, Seitenwände (42a, 42b, 145), welche zusammenhängend entlang einem Innenumfang der Schattenmasken-Anschweißfläche (41) ausgebildet sind, und eine Flanschfläche (43; 43a, 43b), welche entlang den Seitenwänden (42a, 42b, 145) ausgebildet ist, und im wesentlichen parallel zu der Schattenmasken-Anschweißfläche (41) verläuft, aufweist, dadurch gekennzeichnet, daß

die Seitenwände abwechselnd ausgebildete senkrechte Abschnitte (142a, 45b) und schräge Abschnitte (142b, 45a, 45c) aufweisen, und die senkrechten Abschnitte (45b, 142a) im wesentlichen senkrecht zu der Schattenmasken-Anschweißfläche (41) verlaufen, und die schrägen Abschnitte (45a, 142b) so geformt sind,

daß sie gegen die Innenseite des Rahmens (4) geneigt sind; und die Schattenmaske (3) auf der Schattenmasken-Anschweißfläche (41) des Rahmens (4) durch Schweißen in einem Zustand befestigt ist, daß eine vorbestimmte Spannung auf die Schattenmaske (3) ausgeübt wird.

16. Vorrichtung nach Anspruch 15, wobei die Kantenlinien (142c) der schrägen Abschnitte (142b) der Seitenwände (42) im wesentlichen parallel zu den Seiten der Schattenmasken-Anschweißfläche (41) verlaufen, und der schräge Abschnitt (142b), der senkrechte Abschnitt (142a) der Seitenwand (42) und die Flanschfläche (43) eine Öffnung mit einer im wesentlichen dreieckigen Form auf einer Ebene senkrecht zu der Schattenmasken-Anschweißfläche (41) bilden.

17. Vorrichtung nach Anspruch 15 oder 16, wobei sich die Anzahl und/oder die Abmessung des senkrechten Abschnitts (142a) und des schrägen Abschnitts (142b) der Seitenwände (42) an den längeren Seiten von denen an den kürzeren Seiten unterscheiden.

18. Vorrichtung nach Anspruch 15, 16 oder 17, wobei eine Querschnittsform der Seitenwände (42) des Rahmens (4) in der Nähe einer Grenze zwischen der Schattenmasken-Anschweißfläche (41) und den Seitenwänden (42) auf einer Ebene parallel zu der Schattenmasken-Anschweißfläche (41) im wesentlichen achteckig ist.

19. Vorrichtung nach einem der Ansprüche 15 bis 18, wobei der Rahmen (4) in einem Stück durch Preßformung erzeugt ist.

20. Vorrichtung nach Anspruch 15, wobei erste und zweite schräge Abschnitte (45a, 45c) vorgesehen sind und die zweiten schrägen Abschnitte (45c) so ausgebildet sind, daß sie schräg zu der Außenseite des Rahmens (4) verlaufen.

21. Vorrichtung nach Anspruch 20, wobei die Kantenlinien (145a) der Seitenwände (145) und der Schattenmasken-Anschweißfläche (41) gerade Linien sind, und die Kantenlinien (145b) der Seitenwände (145) und der Flanschfläche (43) im wesentlichen Wellenlinien mit abwechselnden Vorzeichen sind.

22. Vorrichtung nach Anspruch 20 oder 21, wobei eine Querschnittsform der Seitenwände (145) des Rahmens (4) in der Nähe einer Grenze zwischen der Schattenmasken-Anschweißfläche (41) und den Seitenwänden (145) auf einer Ebene parallel zu der Schattenmasken-Anschweißfläche (41) im wesentlichen achteckig ist.

23. Vorrichtung nach Anspruch 20, 21 oder 22, wobei der Rahmen (4) in einem Stück durch Preßformung erzeugt ist.
24. Vorrichtung nach einem der Ansprüche 15 bis 23, wobei ein Wärmeausdehnungskoeffizient eines Materials des Rahmens (4) kleiner als der eines Materials der Schattenmaske (3) ist.

Revendications

1. Dispositif à tube à rayons cathodiques couleur comprenant une partie conique (1), un panneau (2), un écran fluorescent (8) disposé à l'intérieur dudit panneau (2), un masque perforé (3) disposé au voisinage dudit écran fluorescent (8), un cadre (4) sur lequel ledit masque perforé (3) est fixé et un canon à électrons (6) disposé dans une partie étroite de ladite partie conique (1) ;

ledit cadre (4) comportant une face de soudure du masque perforé (41) qui présente une forme sensiblement rectangulaire définie par des paires opposées de côtés plus longs et de côtés plus courts, des parois latérales (42a, 42b) qui sont continuellement formées le long d'une périphérie interne de la face de soudure du masque perforé (41) et sont sensiblement perpendiculaires à ladite face de soudure du masque perforé (41) et une face de rebord (43a, 43b) qui est formée le long desdites parois latérales (42a, 42b) et est sensiblement parallèle à ladite face de soudure du masque perforé (41), caractérisé en ce que

ledit masque perforé (3) est fixé sur ladite face de soudure du masque perforé (41) dudit cadre (4) par soudure à condition qu'une tension prédéterminée soit appliquée audit masque perforé (3) ; et au moins un élément de renforcement (44 ; 45 ; 46) est prévu sur ladite face de rebord (43a) de chacun des côtés les plus longs (43a) dudit cadre (4) de sorte qu'une résistance mécanique des cotés les plus longs (42a, 43a) dudit cadre (4) est plus grande que celle des côtés les plus courts (42b, 43b) dudit cadre.

2. Dispositif selon la revendication 1, dans lequel ledit élément de renforcement (45) présente une forme rectangulaire et est monté à l'oblique entre ladite paroi latérale (42a) et ladite face de rebord (43a) dudit cadre (4).
3. Dispositif selon la revendication 1 ou 2, dans lequel un autre élément de renforcement est de plus prévu sur chacun des côtés les plus longs et des côtés les plus courts dudit cadre, mais au moins un élément de la forme, de l'épaisseur du matériau, desdits élé-

ments de renforcement prévus sur les côtés les plus longs est différent de celui desdits éléments de renforcement prévus sur les côtés les plus courts.

4. Dispositif selon la revendication 1, dans lequel ledit élément de renforcement (46) présente une forme sensiblement triangulaire et est monté entre ladite paroi latérale (42a) et ladite face de rebord (43a) et est orienté sensiblement perpendiculaire à ladite face de soudure du masque perforé (41).

5. Dispositif selon la revendication 4, dans lequel au moins un autre élément de renforcement (44 ; 45 ; 46) est de plus prévu sur chacun des côtés les plus longs et des côtés les plus courts dudit cadre, mais au moins un élément de la forme, de l'épaisseur, du nombre et du matériau desdits éléments de renforcement prévus sur les côtés les plus longs est différent de celui desdits éléments de renforcement prévus sur les côtés les plus courts.

6. Dispositif selon l'une quelconque des revendications 1 à 5, dans lequel une largeur (W1) d'au moins une partie de ladite face de rebord (43a) sur chaque côté le plus long dudit cadre (4) est plus large qu'une largeur (W2) de ladite face de rebord (43b) sur chaque côté le plus court dudit cadre (4).

7. Dispositif selon l'une quelconque des revendications 1 à 6, dans lequel ladite paroi latérale 42a sur chaque côté le plus long dudit cadre (4) se bombe vers l'extérieur.

8. Dispositif selon l'une quelconque des revendications 1 à 7, dans lequel au moins une partie de ladite face de rebord (43b) sur chaque côté le plus court dudit cadre (4) est découpé.

9. Dispositif selon l'une quelconque des revendications 1 à 8, dans lequel

ladite face de rebord (43b) sur chaque côté le plus court dudit cadre (4) est recourbée de manière à ce que
une hauteur (H2) à la partie la plus basse de la paroi latérale (42b) sur chaque côté le plus court dudit cadre (4) est plus basse qu'une hauteur de la paroi latérale (42b) sur chaque côté le plus long.

10. Dispositif selon l'une quelconque des revendications 1 à 9, dans lequel lesdits côtés les plus longs (42a, 43a) et lesdits côtés les plus courts (43a, 43b) dudit cadre (4) sont respectivement formés à partir de premier et second éléments indépendants (4a, 4b) et une épaisseur du premier élément (4a) pour ledit côté le plus long est plus grande que celle du second élément (4b) pour ledit côté le plus court.

11. Dispositif selon l'une quelconque des revendications 1 à 9, dans lequel lesdits côtés les plus longs (42a, 43a) et lesdits côtés les plus courts (42b, 43b) dudit cadre (4) sont respectivement formés à partir de premier et second éléments indépendants (4a, 4b) et un matériau dudit premier élément (4a) pour ledit côté le plus long est différent de celui du second élément (4b) pour ledit côté le plus court.

12. Dispositif selon la revendication 11, dans lequel le module d'élasticité dudit matériau dudit premier élément (4a) pour ledit côté le plus long est plus grand que celui dudit second élément (4b) pour ledit côté le plus court.

13. Dispositif selon la revendication 12, dans lequel ladite épaisseur et la forme en section transversale dudit premier élément (4a) sont identiques à celles dudit second élément (4b).

14. Dispositif selon l'une quelconque des revendications 1 à 13, dans lequel un coefficient de dilatation thermique d'un matériau dudit cadre (4) est plus petit que celui d'un matériau dudit masque perforé (3).

15. Dispositif à tube à rayons cathodiques couleur comprenant une partie conique (1), un panneau (2), un écran fluorescent (8) disposé à l'intérieur dudit panneau (2), un masque perforé (3) disposé au voisinage dudit écran fluorescent (8), un cadre (4) sur lequel ledit masque perforé (3) est fixé et un canon à électrons (6) disposé dans une partie étroite de ladite partie conique (1) ;

ledit cadre (4) comporte une face de soudure du masque perforé (41) dans lequel quatre côtés de celui-ci sont formés continuellement en une forme sensiblement rectangulaire définie par des paires opposées de côtés plus longs et plus courts, des parois latérales (42a, 42b ; 145) qui sont formées continuellement le long d'une périphérie interne de ladite face de soudure du masque perforé (41) et une face de rebord (43 ; 43a, 43b) qui est formée le long desdites parois latérales (42a, 42b ; 145) et sensiblement parallèle à ladite face de soudure du masque perforé (41) ;

caractérisé en ce que lesdites parois latérales comportent des parties perpendiculaires (142a, 45b) et des parties inclinées (45a, 45c ; 142b) formées en alternance ;

et lesdites parties perpendiculaires (45b ; 142a) sont sensiblement perpendiculaires à ladite face de soudure du masque perforé (41) et lesdites parties inclinées (45a ; 142b) sont formées pour être inclinées vers l'intérieur dudit cadre (4) ; et

ledit masque perforé (3) est fixé sur ladite face

de soudure du masque perforé (41) dudit cadre (4) par soudage à condition qu'une tension prédéterminée soit appliquée audit masque perforé (3).

16. Dispositif selon la revendication 15, dans lequel des lignes de nervures de renforcement (142c) desdites parties inclinées (142b) desdites parois latérales (42) sont sensiblement parallèles aux côtés de ladite face de soudure du masque perforé (41) et ladite partie inclinée (142b), ladite partie perpendiculaire (142a) de la paroi latérale (42) et ladite face de rebord (43) définissent une ouverture, présentant une forme sensiblement triangulaire sur un plan perpendiculaire à ladite face de soudure du masque perforé (41).

17. Dispositif selon la revendication 15 ou 16, dans lequel au moins un élément du nombre et de la dimension de ladite partie perpendiculaire (142a) de ladite partie inclinée (142b) desdites parois latérales (42) sur lesdits côtés les plus longs est différent de celui sur lesdits côtés les plus courts.

18. Dispositif selon la revendication 15, 16 ou 17, dans lequel une forme en section transversale desdites parois latérales (42) dudit cadre (4) au voisinage d'une frontière entre ladite face de soudure du masque perforé (41) et lesdites parois latérales (42) sur un plan parallèle à ladite face de soudure du masque perforé (41) est sensiblement octogonale.

19. Dispositif selon l'une quelconque des revendications 15 à 18, dans lequel ledit cadre (4) est solidairement formé par travail à la presse.

20. Dispositif selon la revendication 15, dans lequel les première et seconde parties inclinées (45a, 45c) sont prévues et lesdites secondes parties inclinées (45c) sont formées pour être inclinées vers l'extérieur dudit cadre (4).

21. Dispositif selon la revendication 20, dans lequel lesdites lignes de nervures de renforcement (145a) desdites parois latérales (145) et de ladite face de soudure du masque perforé (41) sont des lignes droites et les lignes de nervures de renforcement (145b) desdites parois latérales (145) et ladite face de rebord (43) sont des formes ondulées de signe sensiblement alterné.

22. Dispositif selon la revendication 20 ou 21, dans lequel une forme en section transversale desdites parois latérales (145) dudit cadre (4) au voisinage d'une frontière entre ladite face de soudure du masque perforé (41) et lesdites parois latérales (145) sur un plan parallèle à ladite face de soudure du masque perforé (41) est sensiblement octogonale.

23. Dispositif selon la revendication 20, 21 ou 22, dans lequel ledit cadre (4) est solidairement formé par travail à la presse.

24. Dispositif selon l'une quelconque des revendications 15 à 23, dans lequel un coefficient de dilatation thermique d'un matériau dudit cadre 4 est plus petit que celui d'un matériau dudit masque perforé (3).

10

15

20

25

30

35

40

45

50

55




FIG.1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG.11




FIG. 12




FIG. 13




FIG.14(a)




FIG.14(b)




FIG.14(c)




FIG.15




FIG.16




FIG.17




FIG. 18